



Double-wall DEF Storage Tanks



Tank Dimensions					
Tank Model	DWT 400L	DWT 620L	DWT 1000L	DWT 1000LH	DWT 1500L
Nom. capacity US gal (liters)	110 (400)	165(620)	275 (1000)	275 (1000)	400 (1500)
Length inches (cm)	29 (74)	29 (74)	43 (110)	51 (130)	64 (163)
Width inches (cm)	28 (72)	28 (72)	28 (72)	30 (76)	30 (77)
Height inches (cm)	44 (112)	61 (155)	61 (155)	54 (137)	68 (173)
Min. height required inches (cm)	49 (125)	66 (168)	66 (168)	60 (152)	76 (193)
Tank weight lbs. (kg)	106 (48)	132 (60)	167 (76)	208 (94)	333 (151)
Shipping weight lbs. (kg)	115 (52)	143 (65)	185 (84)	230 (104)	358 (162)



HDPE has been identified as a preferred material for tank construction for DEF storage, transport and handling making the Roth DWT an ideal choice for storage and dispensing.

The Roth DWT double-wall construction with the metallic outer tank provides an ideal package offering both secondary containment and complete protection of the fluid from UV exposure.

Certified to UL SU2258 and compliant with NFPA 30 & 30A.

Key Benefits

- Safest and most reliable tank on the market
- Inner tank made of blow-molded, high-density, seamless polyethylene that is leak-proof and will never corrode
- Outer tank is made of lweld-free galvanized steel and rollseamed with an oil and fire-resistant seal
- Outer tank holds 110 percent of inner tank for maximum protection
- Up to 50 percent lighter than conventional steel tanks
- Can use for DEF, heating oil, diesel and bio fuels, motor oil and ATF
- Compact, economical design (8 sq. ft. for 1000L)
- Wide handles on each end allow you to transport and handle with ease
- Quality control and testing exceeds industry standards