

# Submittal Data Sheet



Part #	Description
2375000103	Mini Mixing Station

## Project Information

Job Name:

Location:

Engineer:

Contractor:

Manufacturer's Representative:

Date Submitted:

Submitted by:

Approved by:

## Application

Provides low temperature radiant floor heat to a small space from a high temperature hydronic system such as baseboard.

## Product Information

- Used in 1 or 2\* loop installations
- Integrated mixing valve
- Remote capillary bulb room temperature sensor
- Non-electric thermostatic controller
- Connects to main system with 1/2" copper compression fittings (included)
- Attaches to PE-RT/PEX tubing using HK manifold fitting assemblies (3/8, 1/2 or 5/8")
- Optional 2-loop adaptor available (2372100020)

## Technical Information

Maximum operating pressure	100 psi (6.9 bar)
Maximum supply water temperature	200°F / 93°C
Maximum radiant water temperature	115°F / 46°C
Electrical - circulator	110v, 1ph, .033HP, 0.23a, 25w
Electrical cord length	40" (1 m)
Sensor capillary tube length	16' (4.9 m)
Thermostatic controller room temperature range ("5" setting is approximately 68°F (20°C))	50°F - 78°F 10°C - 26°C

## Contact Information

Roth Industries, Inc. 268 Bellew Ave. S. Watertown, NY 13601

Telephone: US (888) 266-7684 Canada (800) 969-7684 Fax: US & Canada (866) 462-2914

www.roth-america.com



## Pump Performance Curve

